

# Submittal Data: System 15RLS ASU15RLS & AOU15RLS



Job Name: \_\_\_\_\_ Location: \_\_\_\_\_

Purchaser: \_\_\_\_\_

Engineer: \_\_\_\_\_

Submitted To: \_\_\_\_\_ For:  Reference  Approval  Construction

Submitted By: \_\_\_\_\_

Unit Designation: \_\_\_\_\_ Schedule No. \_\_\_\_\_ Model No.: \_\_\_\_\_

**Capacities:**

Cooling	14,500 BTU/h
Outdoor Design Temp. <i>F° DB/WB</i>	95/75
Heating	18,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
HSPF	11.0
SEER	21.0
EER <i>Cooling/Heating</i>	12.5/12.3
Voltage/Frequency/Phase	208-230/60/1

**Indoor Unit:**

Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	46/ 40/ 33/ 25
Noise Level Heating <i>db (A) - H/ M/ L/ Q</i>	46/ 40/ 35 /26
Weight	18 lbs.

**Outdoor Unit:**

Noise Level <i>Cooling/Heating</i>	51/51
Recommended Fuse Size	20A
Min. Ampacity	10 A
Running Current <i>Cooling</i>	5.2A
Running Current <i>Heating</i>	6.4A
Weight	89 lbs.

**Refrigerant Piping:**

Max Ht. Difference	49 ft.
Max Total or Combined Length	66 ft.
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	3/8 in.

- ◆ Seven year compressor warranty
- ◆ Five year parts warranty
- ◆ Digital wireless remote control
- ◆ 2-way automatic louvers
- ◆ Minimum Heat (50°F heating set point)
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ Sleep timer
- ◆ Optional Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Quiet Mode

**Notes:**

---



---



---

**OUTLINE AND DIMENSIONS**

